

Datasheet

COCOMM CV140



Features

GSM 900/1800 MHz, UMTS 850/1900 MHz and LTE 1/3/7/8/20/28A/38 bands

SIM-in system

VoLTE supported

LTE standard: 3GPP Release 9 CAT4

2 RJ11 ports

Call waiting

Call forwarding

Multi-conference

DTMF dialling

5 LEDs for status indication

Telecare service support

Specifications

Frequencies	GSM 900/1800 MHz UMTS 850/1900 MHz LTE 1/3/7/8/20/28A/38 bands
Antenna	External
Processor	UNISOC T117 + SC2332B OS: RTOS
Battery	Type: Li-ion Capacity: 4000 mAh Talk time: 6 hours Standby time: 72 hours Charge time: 3-4 hours
Connectivity	Wi-Fi Hotspot* (*upon customer request)
Connections	DC jack charging connector 2 RJ11 ports for FXS Micro USB 2.0 for SW upgrade Reset button Power button
Leds	Charge indicator SIM card indicator Battery indicator Alarm and voice indicator Coverage indicator
Security	Battery compartment with secured screw

Supported services	Call services: call forwarding, call waiting, transfer and conference Telecare via DTMF commands (in-band and out-of-band) Caller ID (on supported terminals) High quality voice services support (FR, EFR, HR, AMR) Blacklist/Whitelist Alarm Emergency calls Telecare support Remote software update via FOTA Voice command response Management from PC (UCC Suite)
Certifications	GCF, CE and RoHS (among others)
Dimensions	122x147x32 mm
Weight	321 g
Sales package content	Main unit External antenna Charger Battery User manual Warranty Card Security screw and key
